## <u>UCEL Sample Questions: Cite articles or tables from 2017 NFPA 70 NEC</u> <u>Each questions is worth 5 points, multiple choice (Circle 1) = 2 points, Citing = 3 points</u>

1) W	nich of the following type conductor insulation cal	nnot be use	ea in wet	locations?
Α.	THHN	C.	THHV	v
В.	THWN	D.	THW	
Citin	g:			
	ne maximum distance from an outlet box that flexi		onduit m	nust be secured?
Α.	18 inches	c.	24 in	ches
В.	12 inches	D.	36 inches	
Citin	g:			
3) Th	ne maximum spacing between supports for 1-1/4 in	nch, PVC co	nduit is?	,
Α.	2 ft.	c.	3 ft.	
В.	4 ft.	D.	5 ft.	
Citin	g:			
4) W	hich of these cable types are nonmetallic-sheather	d cable?		
A.	NM	c.	AC	
В.	SJO	D.	USE	
Citin	g:			
	hen NM cable enters into a non-metallic outlet bo		r coverin	g must?
Α.	Extend into the box not less than 1/4 inch	C.	Extend into the box not less than 1/2 inc	
В.	End flush with the point of entry	D.	Exter	nd to the connection points
Citin	g:			
6) W	hat is the minimum depth that an outlet box can b	e if it does	not encl	ose devices?
A.	1 inch		C.	1-1/4 inch
В.	1/2 inch		D.	1-1/2 inch
Citin	g:			
7) Th	ne minimum allowable horizontal clearance for ove	erhead serv	ice cond	uctors from a swimming pool is?
Α.	6 feet		C.	10 feet
В.	8 feet		D.	12 feet
Citin	g:			
8) W	here in the 2017 NEC would you find the correctio	n factors fo		t-carrying conductors where more
tnan	3 are bundled together for a distance greater than	24 inches:		
A.	Chapter 9, table 4		C.	Annex C.10
В.	Chapter 9, table 9		D.	Table 310.15(B)(3)(A
	g:			
	ted or labeled equipment shall be installed and uson ded in the listing or labeling?	ed in accor	dance wi	ith any
Α.	Exceptions		C.	Additional requirements
В.	Instructions		D.	Other documents
Citi				